

Techsense Bangladesh Ltd

Rotary Actuators Series R3, Code- W1630306180

Actuator with double rack and play take-up. Angle of rotation adjustable from 0 to 180°. The R3 rotary actuator can come with a mechanical stop or hydraulic end-of-stroke cushioning. There is a version with flange and one with shaft (for $\varnothing 16-20-25-30$). There are slots in the body for retracting magnetic proximity sensors, two on each side. There is hole in the flange for air pipes or wires.

TECHNICAL DATA		R3-16	R3-20	R3-22	R3-25	R3-30	R3-40
Operating pressure	bar	3 to 7					
	MPa	0.3 to 0.7					
	psi	43.5 to 101					
Temperature range	°C	-10 to +80					
Angle adjustment	degrees	0° to 180°					
Fluid		20 μ m filtered, lubricated or unlubricated air; lubrication if used, it must be continuous					
Versions		With mechanical stop / hydraulic decelerator					
Sizes		16	20	22	25	30	40
Bores	mm	2 x 16	2 x 20	2 x 22	2 x 25	2 x 30	2 x 40
Theoretical torque at 6 bar	Nm	0.9	1.8	2.7	4.6	9.3	22
Max. axial load	N	74	135	195	300	340	360
Max. radial load	N	78	137	360	450	490	560
Weight	kg	0.53	0.99	1.29	2.08	3.9	6.7
Rotation time without load	s	0.2	0.2	0.2	0.2	0.3	0.3
Admissible kinetic energy	Joule						
WITH MECHANICAL STOP (with flange W1630__2180 and with shaft W1630__5180)		0.007	0.025	0.049	0.082	0.090	0.150
WITH HYDRAULIC DECELERATOR (with flange W1630__2180 and with shaft W1630__5180)		-	-	-	0.29	1.10	1.60

General Attributes

- Type : with shaft + shock absorbers R3-180
- Diameter (Bore) : 30 mm




COMPONENTS

- ① ROTARY FLANGE: anodised aluminium
- ② PINION: hardened and tempered steel
- ③ BALL BEARING
- ④ PISTON / RACK: hardened and tempered steel
- ⑤ CUSHIONING GASKET: NBR
- ⑥ GUIDE SHOE: PTFE
- ⑦ MAGNET: neodymium
- ⑧ HEAD: anodised aluminium
- ⑨ BARREL: anodised aluminium
- ⑩ SEAL: NBR

VERSIONS:

- Ⓐ Stroke adjustment
- Ⓑ Stroke adjustment with inside hydraulic shock absorbers (available from $\varnothing 25$)



For further information please visit : <https://goo.gl/wfoWWW>



LISTED IND. CONT. EQ. 81U2
 for use in the secondary of
 a class 2 source of supply

We are the authorized distributor of Metal Work in Bangladesh.



IND. CONT. EQ
 81U2
 for use in the secondary of
 a class 2 source of supply
 Environmental - Type 1 Enclosure

